

Product Data

BP Autran Syn 295

Premium Heavy Duty ATF

Description

BP Autran Syn 295 is a fully synthetic universal shift and automatic transmission fluid designed to increase efficiency through extended drain intervals. BP Autran Syn 295 is formulated to maintain its stability even under the most severe operating conditions.

Application

BP Autran Syn 295 can be used in a variety of applications including:

- Inter/intra-city buses, school buses
- · Delivery trucks and vans
- · Refuse fleets
- Emergency vehicles
- Light duty pickup trucks and passenger cars (where DEXRON®-III is approved)
- Recreational vehicles/motor homes
- On/Off-highway vehicles

Advantages

- Superior high/low temperature performance due to high VI synthetic base fluids
- Excellent shear stability provides a stable viscosity, providing wear protection throughout the drain interval
- Excellent corrosion and foaming resistance
- · Allows for extended drain intervals and extended filter change intervals reducing operating costs
- Compatible with most other automotive transmission fluids and seals
- Offers flexibility of one fluid for year-round use in all geographic locations
- Provides durable and consistent transmission shifts
- Provides excellent thermal and oxidation stability resulting in lower deposit formation

Typical Physical Characteristics

| Test | Method | Typical Results |
|------------------------------------|-------------|-----------------|
| Viscosity at 40°C, cSt | ASTM D-445 | 37.7 |
| Viscosity at 100°C, cSt | ASTM D-445 | 7.35 |
| Viscosity Index | ASTM D-2270 | 165 |
| Color, Typical | ASTM D-1500 | 7.0 |
| Appearance | | Red |
| Brookfield Viscosity at -40 C, cP | ASTM D-2983 | 8,150 |
| Pour Point, °C (°F) | ASTM D-97 | -60 (-76) |
| Flash Point, °C (°F) | ASTM D-92 | 235 (455) |
| Specific Gravity, 60°F | ASTM D-1298 | 0.845 |
| Pounds per Gallon | ASTM D-287 | 7.03 |
| KRL Shear 20 Hrs, % Viscosity Loss | CEC-L45 A | 3.8 |
| Rust Protection | ASTM D1748 | No Rust |

Product Performance Claims

BP Autran Syn 295 meets or exceeds the performance requirements set forth by OEMs and is listed and approved under the following specifications:

- Allison TES-295 (AN-031002)
- Allison TES-468
- Allison C-4 (33014203)
- ZF TE-ML 14C
- Voith H55.633636 (G-34010)
- DEXRON[®]-IIIG (G-34746)

Additional Information

Part Numbers and UPCs

| | BP Autran 295 Syn |
|-----------------------|-------------------|
| 6 x 1 Gal Case Part # | 709732 |
| 5 Gal Pail Part # | 709707 |
| 55 Gal Drum Part # | 709701 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDSs are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Autran Syn 295 28 Mar 2013

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com